

WORLD INTELLECTUAL PROPERTY ORGANIZATION INICIALIDAL BUTCHU



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:	١	(11) International Publication Number: WO 98/43071
G01N 21/27, 21/31	A1	(43) International Publication Date: 1 October 1998 (01.10.98)
(21) International Application Number: PCT/IB (22) International Filing Date: 21 March 1997 (CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL
(71) Applicant: NELLCOR PURITAN BENNETT INC. 4280 Hacienda Drive, Pleasanton, CA 94588 (US)	เกรงกร	
(72) Inventors: BAKER, Clark, R., Jr.; 18493 Magee Wa Valley, CA 94546 (US). YORKEY, Thomas, Bernard Avenue, San Ramon, CA 94583 (US).	y, Cast J.; 30	70 72
	-	

(54) Tile: METHOD AND APPARATUS FOR ARBITRATING TO OBTAIN BEST ESTIMATES FOR BLOOD CONSTITUENT VALUES AND REJECTING HARMONICS

(57) Abstract

A method of measuring a blood constituent value using data comprising a single data set comprises: (a) determining a plurality of possible blood constituent values using a phurality of blood constituent value calculators, each of the blood constituent value calculators using the single data set, each of the possible blood constituent values having a confidence level associated therewith based on at least one quality metric; and (b) arbitrating between the plurality of possible blood constituent values with regard to the confidence levels to determine a measure of the blood constituent.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		•	•				· •
٨L	Albenia	E S	Spále	LS	Lexitho	SI	Slovenia
AM		FI	Flatend	. UT	Lithuseis	536	Stovakia
AT	Austria	22	France	ᄲ	Luxembourg	SM	Scaogal
AU	Aystralia	GA	Cabon	FA	Latyla	5 18	Swariband
ÄZ	Azerbeijen	GB	United Kingdom	MC	Monaco	TD	Ched
DA	Bossia and Herzegovina	GE	Goorgie	MD	Republic of Moldova	TG	Togo
88	Barbados	CH	Chame	MG	Madagaseur	TJ	Teffician
20	Belgiam	GS4	Gelota	MK	The former Yogoslav	TM	Testanosima
BP	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Rungary	ML	Mail	TT	Trinidad and Tobego
BJ.	Benta	18	Ireland	MN	Mongolia	UX	Ukraine
BR	Bracil	n.	besel	MR	Marritona.	UG	Uganda
		IS	lectand .	MW	Malavi	US	United States of America
BY	. Belarus	Ħ	Daly	MX	Mexico	UZ	Uzhekletan
CA	Canada			NE	Niger	ΥN	Viet Nam
CI.	Central African Republic	n	Japan	NL	Nederlands	YU	Yegoslavia
CG	Congo	K	Kenya		Normy	ZW	Zirsbabwe
CR	S witzerbo ud _	KG	Кугдугана	МО	New Zestand		
CI	Colo d'Iroise	KP	Democratic People's	NZ			•
CM	Carneroon		Republic of Korea	PL	Puband		
CN	China	KR	Republic of Korea	PT	Portugui		
CU	Cobs	KZ	(Cazalistan	· RO	Romania		
Œ	Crech Republic	LC	Saint Lucia	RU	Russian Federation		
DE		u	Liechtenstela	SD	Sudan		
DK		LK	Sri Lenica	\$ E	Sweden		
EE	Exonia	LR	Liberia	SG	Shigapore		

MAS 77824 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22494

METHOD AND APPARATUS FOR ARBITRATING TO OBTAIN BEST ESTIMATES FOR BLOOD CONSTITUENT VALUES & REJECTING HARMONICS

This invention relates to a method and apparatus for measuring physiological parameters, in particular for processing data so that its reliability can be assessed. It relates in particular to a method and apparatus for arbitrating to obtain best estimates for blood constituent values and rejecting harmonics.

Pulse oximeters typically measure and display various blood flow characteristics including the oxygen saturation of haemoglobin in arterial blood and pulse rate. Oximeters pass light through blood perfused tissue such as a finger or an ear, and photoelectrically sense the absorption of light in the tissue. The amount of light absorbed is then used to calculate the amount of the blood constituent (for example oxyhaemoglobin) being measured.

Techniques for calculating blood oxygen saturation levels in haemoglobin are disclosed in International patent application no. IB96/ filed with the present application entitled METHOD AND APPARATUS FOR ADAPTIVELY AVERAGING DATA SIGNALS, which bears the reference P21977A. Information concerning these features of the present invention that is disclosed in those documents is incorporated in the specification of the present application by this reference. The disclosed technique involves assigning varying weights to different measurements, the weighted measurements being averaged to obtain a filtered It employs Kalman filtering techniques to measurement. calculate blood oxygen saturation. Kalman filtering allows one to fit parameters in a least squares sense when the parameters are varying in time.

Other techniques for calculating blood oxygen saturation levels in haemoglobin, in which a harmonic filter is used to reduce noise effects, are disclosed in International patent application no. IB96/ filed with the present application entitled METHOD AND APPARATUS FOR HARMONICALLY FILTERING DATA,

MAS 77826 CONFIDENTIAL ATTORNEYS EYES ONLY

entitled METHOD AND APPARATUS FOR HARMONICALLY FILTERING DATA, which bears the reference P21977D. Information concerning these features of the present invention that is disclosed in that document is incorporated in the specification of the present application by this reference.

Techniques for determining pulse rates are disclosed in International patent application no. IB96/ filed with the present application entitled METHOD AND APPARATUS FOR MEASURING PULSE RATE AND SATURATION, which bears the reference P21977B. Information concerning these features of the present invention that is disclosed in this document is incorporated in the specification of the present application by this reference. A technique disclosed in the document involves use of a comb filter to isolate signal energy which corresponds to fundamental and related frequencies.

The present invention provides a technique for assessing signals relating to physiological parameters, in particular blood oxygen saturation and pulse rate, to determine whether and how they are to be displayed. The signals can be derived using techniques of the type that are disclosed in the specifications of the three applications referred to above. The technique of the invention involves arbitrating between possible values of the parameter in question according to a confidence level associated with each value based in a quality metric.

Accordingly, in one aspect, the invention provides a method of measuring a blood constituent value (for example, oxygenated haemoglobin in blood) using data comprising a single data set, which comprises:

(a) determining a plurality of possible blood constituent values using a plurality of blood constituent value calculators, each of the blood constituent value calculators using the single data set, each of the

MAS 77826 CONFIDENTIAL ATTORNEYS EYES ONLY

possible blood constituent values having a confidence level associated therewith based on at least one quality metric; and

(b) arbitrating between the plurality of possible blood constituent values with regard to the confidence levels to determine a measure of the blood constituent.

In another aspect, the invention provides apparatus for measuring a blood constituent using a single data set, by applying the method referred to above.

In a further aspect, the invention provides a method of determining a patient's pulse rate using data comprising a single data set corresponding to electromagnetic energy transmitted through the tissue of a patient, the method comprising the steps of:

- (a) determining a plurality of possible pulse rates using a plurality of pulse rate estimators, each of the pulse rate estimators using the single data set, each of the possible pulse rates having a confidence level associated therewith based on at least one quality metric; and
- (b) arbitrating between the plurality of possible pulse rates with regard to the confidence levels to determine the patient's pulse rate.

In yet another aspect, the invention provides apparatus for determining a patient's pulse rate using a single data set, by applying the method referred to above.

Preferably, the arbitrating step comprises:

(a) comparing the confidence levels for each of the values with the confidence levels for other values; and

MAS 77827 CONFIDENTIAL ATTORNEYS EYES ONLY

(b) selecting as the measure of the blood constituent or of the pulse rate (as the case may be) one of the plurality of possible values having a confidence level greater than all other confidence levels by at least a first amount.

Preferably, the arbitrating step comprises linearly interpolating between the plurality of possible values to generate the measure of the blood constituent or the patient's pulse rate (as the case may be) where none of the confidence levels is greater than all other confidence levels by more than a first amount.

When the method is measuring a blood constituent value, it is preferred that the quality metric is selected from the group comprising age of the possible blood constituent value and variance of the possible blood constituent value.

Preferably, in the second method aspect of the invention, the pulse rate estimator determines its corresponding possible pulse rate by:

- (a) defining a comb filter to remove signal energy from the data corresponding to a fundamental frequency and harmonics thereof;
- (b) determining a particular harmonic frequency which minimizes noise energy at an output of the comb filter, the particular harmonic frequency corresponding to the fundamental frequency; and
- (c) generating the possible pulse rate corresponding to the particular harmonic frequency.

Preferably, the step of determining the harmonic frequency comprises:

(a) calculating squared noise for the data;

MAS 77828 CONFIDENTIAL ATTORNEYS EYES ONLY

- (b) calculating a second derivative of the squared noise with respect to the fundamental frequency; and
- (c) performing a Newton-Raphson search to determine the particular harmonic frequency.

The determination of the pulse rate by the pulse rate estimator can include the steps of:

- (a) evaluating a power spectrum corresponding to the data to determine which of a plurality of peaks in the power spectrum corresponds to the fundamental frequency; and
- (b) verifying that the particular harmonic frequency corresponds to the fundamental frequency based on the evaluating step.

When the method is determining a patient's pulse rate, it is preferred that the quality metric is selected from the group comprising pulse signal shape, signal-to-noise ratio, correlation of the at least one wavelength of electromagnetic energy, arrhythmia probability, and, when there are two wavelengths of electromagnetic energy, a correlation between the data corresponding to the two wavelengths.

The pulse rate estimator in the second method aspect of the invention can determine its corresponding possible pulse rate by:

- (a) comparing the data to a predetermined waveform template;
- identifying a sequence of waveform characteristics indicative of a waveform period;
- (c) averaging a number of successive waveform periods to determine an average waveform period; and
- (d) determining the corresponding possible pulse rate from the average waveform period.

MAS 77829 CONFIDENTIAL ATTORNEYS EYES ONLY The method can include a step of identifying pulse data that is corrupted by motion, and rejecting that data.

The quality metric can then be selected from the group comprising a motion indication, and a proportion of motion corrupted pulse periods detected over a time interval.

In a yet further aspect, the invention provides a method of determining a pulse rate of a patient using data corresponding to at least one wavelength of electromagnetic energy transmitted through tissue of the patient, which comprises:

- (a) tracking a fundamental frequency using an adaptive comb filter to filter the data and to thereby generate a first pulse rate, the first pulse rate having a first confidence level associated therewith based on at least one quality metric;
- (b) comparing the data to a predetermined waveform template to generate a second pulse rate, the second pulse rate having a second confidence level associated therewith based on the at least one quality metric; and
- (c) arbitrating between the first and second pulse rates with regard to the first and second confidence levels to determine the patient's pulse rate.

Preferably, the tracking step comprises:

- (a) defining a comb filter to remove signal energy from the data corresponding to the fundamental frequency and harmonics thereof; and
- (b) determining a particular harmonic frequency which minimizes noise energy at an output of the comb filter, the particular harmonic frequency corresponding to the fundamental frequency.

MAS 77830 CONFIDENTIAL ATTORNEYS EYES ONLY Preferably, the step of determining the harmonic frequency then comprises:

- (a) calculating squared noise for the data;
- (b) calculating a second derivative of the squared noise with respect to the fundamental frequency; and
- (c) performing a Newton-Raphson search to determine the fundamental frequency.

The tracking step can comprise:

- (a) evaluating a power spectrum corresponding to the data to determine which of a plurality of peaks in the power spectrum corresponds to the fundamental frequency; and
- (b) verifying that the particular harmonic frequency corresponds to the fundamental frequency based on the evaluating step.

It might also include a step of filtering the first pulse rate to determine a filtered first pulse rate, for example by a filtering technique such as Kalman filtering.

Preferably, the comparing step of the method comprises:

- identifying a sequence of waveform characteristics indicative of a waveform period;
- (b) averaging a number of successive waveform periods to determine an average waveform period; and
- (c) determining the second pulse rate from the average waveform period.

Preferably, the arbitrating step of the method comprises:

(a) comparing the first and second confidence levels;and

MAS 77831 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22501

(b) selecting as the patient's pulse rate one of the first and second confidence levels which is greater than the other of the first and second confidence levels by at least a first amount.

The arbitrating step can comprise linearly interpolating between the first and second pulse rates to generate the patient's pulse rate where neither of the first and second confidence levels is greater than the other of the first and second confidence levels by more than a first amount.

Preferably, the at least one quality metric corresponding to the first confidence level is selected from the group comprising pulse signal shape, signal-to-noise ratio, correlation of the at least one wavelength of electromagnetic energy, and arrhythmia probability.

Preferably, there are two wavelengths of electromagnetic energy, and the at least one quality metric corresponding to the first confidence level comprises a correlation between the data corresponding to the two wavelengths.

Preferably, the at least one quality metric corresponding to the second confidence level is selected from the group comprising a motion indication, and a proportion of motion corrupted pulse periods detected over a time interval.

Preferably, prior to the processing step, the method includes the steps of:

- taking the logarithm of a signal representative of the at least one wavelength of electromagnetic energy, thereby generating a first signal;
- (b) band pass filtering the first signal, thereby generating a second signal; and
- (c) normalizing the second signal, thereby generating the data;

MAS 77832 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22502

the tracking step comprising taking the derivative of the data.

The invention can involve reduction of noise effects when measuring a physiological parameter. It can include apparatus for reducing the noise effects which comprises:

means for generating a plurality of measurements derived from at least one wavelength of electromagnetic energy transmitted through living tissue;

means for providing a signal indicative of the at least one wavelength of electromagnetic energy;

means for comparing selected measurements with at least one expected measurement characteristic;

means for assigning one of a plurality of variable weights to each selected measurement based on the comparing step thereby generating a plurality of differently weighted measurements for each wavelength, the variable weights being assigned, in part, in response to a similarity between each selected measurement and a corresponding previous measurement, the variable weights comprising a plurality of different non-zero numbers;

means for averaging a plurality of the differently weighted measurements to obtain a filtered measurement for use in estimating the physiological parameter; and

means for calibrating the system to measure the physiological parameter in response to the signal indicative of the at least one wavelength of electromagnetic energy.

The invention also includes a monitor for measuring a physiological parameter, the monitor being for use with a sensor having emitting means for emitting at least one wavelength of electromagnetic energy, sensing means for sensing the electromagnetic energy and for generating a first signal representative thereof, means for detachably coupling the sensor to the oximeter and for providing communication of signals between the sensor and the oximeter, and means for providing a second signal indicative of the at least one wavelength of electromagnetic energy, the monitor comprising:

MAS 77833 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22503

means for generating a plurality of measurements derived from the first signal;

means for comparing selected measurements with at least one expected measurement characteristic;

means for assigning one of a plurality of variable weights to each selected measurement based on the comparing step thereby generating a plurality of differently weighted measurements, the variable weights being assigned, in part, in response to a similarity between each selected measurement and a corresponding previous measurement, the variable weights comprising a plurality of different non-zero numbers;

means for averaging a plurality of the differently weighted measurements to obtain a filtered measurement for use in estimating the physiological parameter; and

means for calibrating the monitor to measure the physiological parameter in response to the second signal.

There now follows a discussion of preferred methods of processing and displaying the blood oxygen saturation and pulse rate for use on a hospital floor. With metrics that are available from algorithms for measuring oxygen saturation levels and pulse rates, confidence levels for the saturation and the pulse rate values that are calculated can be estimated, thus determining which saturation and which pulse rate of the multiple pulse rates and multiple saturations can be considered reliable, and how long the saturation or pulse rate previously selected should be held when a current estimate is not considered sufficiently reliable.

The present invention can be applied to blood oxygen saturation values calculated using Kalman filtering techniques (with or without cardiac gated averaging) as disclosed in the International patent application no. IB96/ (P21977A) referred to above. Metrics that can be calculated from these algorithms include:

Age:

effective averaging period is double this; and

MAS 77834 CONFIDENTIAL ATTORNEYS EYES ONLY

-11-

Deviation: standard deviation of saturation estimate in saturation points.

The present invention can be applied to pulse rate values calculated using a comb filter as disclosed in the International patent application no. [] referred to above. Metrics that can be calculated from these algorithms include:

Validity:

a heuristic metric based on the strength of harmonics in the pulse, i.e., the shape of the pulse;

S/N:

signal-to-noise ratio;

Arrhythmia probability:

a function of S/N vs. Uncorrelation averaged over time; and

Uncorrelation (IR & red)

√1-crosscorrelation (IR, red)² where crosscorrelation is over an appropriate number of sample points.

Motion flag:

set when motion is detected; and

Motion Percent:

percentage of motion corrupted patterns detected in the last ten seconds.

The confidence interval for a pulse rate measured using an adaptive comb filter is a function of the validity metric and the arrhythmia probability metric. This space divides into several regions in which one or both metrics are the determining factor in how likely the adaptive comb filter is to be tracking the correct rate.

The Age and Deviation metrics can be used to determine saturation. A general algorithm for calculating the age of the output of an IIR filter having the form

Filtered(n+1) = (1 + W) * Filtered(n) - W * Raw,

MAS 77835 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22505

where the age of Filtered and Raw are known, and Filtered(n) is the value at sample number n, is described by the following steps:

1) Increment the age of Filtered by the amount of time elapsed since it was last calculated; and

2) Age of Filtered(n + 1) = (1 + W) * Age of
Filtered(n) + W * Age of Raw

Preferably, the technique of the invention involves evaluation of several properties of the incoming oximetry signal, independent of the confidence metrics for the parameter in question (for example oxygen saturation and pulse rate) to determine whether the signal is actually due to a human pulse and what should appear on the display that is provided. Possible states include:

Disconnect: when the sensor is unplugged;

No Contact: when the sensor does not make sufficient

contact with the patient;

Pulse lost: when the pulse disappears and the sensor

is still on the patient;

Non-pulse: when the oximetry signal comes from a

signal other than a human pulse because the sensor has fallen off or is seeing an

enormous amount of interference;

Pulse Present: when the oximetry signal comes from a

human pulse; and

Not Sure: a waiting period before declaring a

Disconnect or Non-pulse state.

The possible actions in response to the occurrence of these various states are to update the display, hold the current values, or clear the display, for example blanks, dashes, zeroes, etc.

The criteria for the various states are evaluated in the following order:

MAS 77836 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22506

-13-

Pulse lost:

The % IR modulation is below a threshold for period of seconds, or the criteria for Non-pulse are met and the previous state had been Pulse lost.

Non-pulse:

The uncorrelation is high and the percentage of energy above 5 Hz is high, OR the percent IR modulation is low. This criterion has been true for ten seconds continuously. If this criterion has been true for less than ten seconds, the Not Sure state is declared.

Pulse present:

The state is not one of the above states.

The criteria for the various display actions are UPDATE when the state is Pulse present, HOLD when the state is Not Sure or No contact, and CLEAR when the state is Disconnect, Pulse lost, or Non-pulse.

The best saturation is displayed when 1) the signal state action is UPDATE, and 2) the best saturation is sufficiently recent. Saturation is held when 1) the conditions for displaying the best saturation are not met, 2) the displayed saturation is less than sufficiently recent, and 3) the signal state action is not CLEAR. Saturation is blanked when 1) the conditions for displaying the best saturation are not met, and 2) the conditions for holding the saturation are not met.

The best heart rate is displayed when 1) the best calculated heart rate has a high confidence, and 2) the signal state action is UPDATE. The heart rate is held when 1) the conditions for displaying the current heart rate are not met, 2) the displayed heart rate is sufficiently recent, and 3) the signal state action is not CLEAR. The heart rate is blanked when 1) the conditions for displaying the current heart rate are not met, and 2) the conditions for holding the heart rate are not met.

MAS 77837 CONFIDENTIAL ATTORNEYS EYES ONLY

CLAIMS:

- 1. A method of measuring a blood constituent value using data comprising a single data set, which comprises:
 - (a) determining a plurality of possible blood constituent values using a plurality of blood constituent value calculators, each of the blood constituent value calculators using the single data set, each of the possible blood constituent values having a confidence level associated therewith based on at least one quality metric; and
 - (b) arbitrating between the plurality of possible blood constituent values with regard to the confidence levels to determine a measure of the blood constituent.
- 2. A method as claimed in claim 1, in which the arbitrating step comprises:
 - (a) comparing the confidence levels for each of the possible blood constituent values with the confidence levels for other blood constituent values; and
 - (b) selecting as the measure of the blood constituent one of the plurality of possible blood constituent values having a confidence level greater than all other confidence levels by at least a first amount.
- 3. A method as claimed in claim 1, in which the arbitrating step comprises linearly interpolating between the plurality of possible blood constituent values to generate the measure of the blood constituent where none of the confidence levels is greater than all other confidence levels by more than a first amount.

MAS 77838 CONFIDENTIAL ATTORNEYS EYES ONLY

- 4. A method as claimed in claim 1, in which the at least one quality metric is selected from the group comprising age of the possible blood constituent value and variance of the possible blood constituent value.
- 5. A method as claimed in claim 1, in which the blood constituent comprises oxygenated haemoglobin in arterial blood.
- 6. Apparatus for measuring a blood constituent using a single data set, comprising:
 - (a) means for determining a plurality of possible blood constituent values using a plurality of blood constituent value calculators, each of the blood constituent value calculators using the single data set, each of the possible blood constituent values having a confidence level associated therewith based on at least one quality metric; and
 - (b) means for arbitrating between the plurality of possible blood constituent values with regard to the confidence levels to determine a measure of the blood constituent.
- 7. A method of determining a patient's pulse rate using data comprising a single data set corresponding to energy transmitted through the tissue of a patient, the method comprising the steps of:
 - (a) determining a plurality of possible pulse rates using a plurality of pulse rate estimators, each of the pulse rate estimators using the single data set, each of the possible pulse rates having a confidence level associated therewith based on at least one quality metric; and

MAS 77839 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22509

- (b) arbitrating between the plurality of possible pulse rates with regard to the confidence levels to determine the patient's pulse rate.
- 8. A method as claimed in claim 7, in which the arbitrating step comprises:
 - (a) comparing the confidence levels for each of the possible pulse rates with the confidence levels for other possible pulse rates; and
 - (b) selecting as the patient's pulse rate one of the plurality of possible pulse rates having a confidence level greater than all other confidence levels by at least a first amount.
- 9. A method as claimed in claim 7, in which the arbitrating step comprises linearly interpolating between the plurality of possible pulse rates to generate the patient's pulse rate where none of the confidence levels is greater than all other confidence levels by more than a first amount.
- 10. A method as claimed in claim 7, in which one pulse rate estimator determines its corresponding possible pulse rate by:
 - (a) defining a comb filter to remove signal energy from the data corresponding to a fundamental frequency and harmonics thereof;
 - (b) determining a particular harmonic frequency which minimizes noise energy at an output of the comb filter, the particular harmonic frequency corresponding to the fundamental frequency; and
 - (c) generating the possible pulse rate corresponding to the particular harmonic frequency.

MAS 77840 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22510

- 11. A method as claimed in claim 10, in which the determining step comprises:
 - (a) calculating squared noise for the data;
 - (b) calculating a second derivative of the squared noise with respect to the fundamental frequency; and
 - (c) performing a Newton-Raphson search to determine the particular harmonic frequency.
- 12. A method as claimed in claim 10 further comprising the steps of:
 - (a) evaluating a power spectrum corresponding to the data to determine which of a plurality of peaks in the power spectrum corresponds to the fundamental frequency; and
 - (b) verifying that the particular harmonic frequency corresponds to the fundamental frequency based on the evaluating step.
- 13. A method as claimed in claim 10, in which the at least one quality metric is selected from the group comprising pulse signal shape, signal-to-noise ratio, correlation of the at least one wavelength of electromagnetic energy, and arrhythmia probability.
- 14. A method as claimed in claim 10, in which there are two wavelengths of electromagnetic energy, and the at least one quality metric comprises a correlation between the data corresponding to the two wavelengths.
- 15. A method as claimed in claim 7, in which one pulse rate estimator determines its corresponding possible pulse rate by:

MAS 77841 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22511

- (a) comparing the data to a predetermined waveform template;
- (b) identifying a sequence of waveform characteristics indicative of a waveform period;
- (c) averaging a number of successive waveform periods to determine an average waveform period; and
- (d) determining the corresponding possible pulse rate from the average waveform period.
- 16. A method as claimed in claim 15, in which the at least one quality metric is selected from the group comprising a motion indication, and a proportion of motion corrupted pulse periods detected over a time interval.
- 17. A method of determining a pulse rate of a patient using data corresponding to at least one wavelength of electromagnetic energy transmitted through tissue of the patient, which comprises:
 - (a) tracking a fundamental frequency using an adaptive comb filter to filter the data and to thereby generate a first pulse rate, the first pulse rate having a first confidence level associated therewith based on at least one quality metric;
 - (b) comparing the data to a predetermined waveform template to generate a second pulse rate, the second pulse rate having a second confidence level associated therewith based on the at least one quality metric; and
 - (c) arbitrating between the first and second pulse rates with regard to the first and second confidence levels to determine the patient's pulse rate.



- 18. A method as claimed in claim 17, in which the tracking step comprises:
 - (a) defining a comb filter to remove signal energy from the data corresponding to the fundamental frequency and harmonics thereof; and
 - (b) determining a particular harmonic frequency which minimizes noise energy at an output of the comb filter, the particular harmonic frequency corresponding to the fundamental frequency.
- 19. A method as claimed in claim 18, in which the determining step comprises:
 - (a) calculating squared noise for the data;
 - (b) calculating a second-derivative of the squared noise with respect to the fundamental frequency; and
 - (c) performing a Newton-Raphson search to determine the fundamental frequency.
- 20. A method as claimed in claim 18, in which the tracking step comprises:
 - (a) evaluating a power spectrum corresponding to the data to determine which of a plurality of peaks in the power spectrum corresponds to the fundamental frequency; and
 - (b) verifying that the particular harmonic frequency corresponds to the fundamental frequency based on the evaluating step.

MAS 77843 CONFIDENTIAL ATTORNEYS EYES ONLY

- 21. A method as claimed in claim 17, in which the tracking step comprises Kalman filtering the first pulse rate to determine a filtered first pulse rate.
- 22. A method as claimed in claim 17, in which the comparing step comprises:
 - (a) identifying a sequence of waveform characteristics indicative of a waveform period;
 - (b) averaging a number of successive waveform periods to determine an average waveform period; and
 - (c) determining the second pulse rate from the average waveform period.
- 23. A method as claimed in claim 17, in which the arbitrating step comprises:
 - (a) comparing the first and second confidence levels; and
 - (b) selecting as the patient's pulse rate one of the first and second confidence levels which is greater than the other of the first and second confidence levels by at least a first amount.
- 24. A method as claimed in claim 17, in which the arbitrating step comprises linearly interpolating between the first and second pulse rates to generate the patient's pulse rate where neither of the first and second confidence levels is greater than the other of the first and second confidence levels by more than a first amount.
- 25. A method as claimed in claim 17, in which the at least one quality metric corresponding to the first confidence level is selected from the group comprising pulse signal shape,

MAS 77844 CONFIDENTIAL ATTORNEYS EYES ONLY

JA 22514

signal-to-noise ratio, correlation of the at least one wavelength of electromagnetic energy, and arrhythmia probability.

- 26. A method as claimed in claim 17, in which there are two wavelengths of electromagnetic energy, and the at least one quality metric corresponding to the first confidence level comprises a correlation between the data corresponding to the two wavelengths.
- 27. A method as claimed in claim 17, in which the at least one quality metric corresponding to the second confidence level is selected from the group comprising a motion indication, and a proportion of motion corrupted pulse periods detected over a time interval.
- 28. A method as claimed in claim 17, which includes, before the processing step, the steps of:
 - (a) taking the logarithm of a signal representative of the at least one wavelength of electromagnetic energy, thereby generating a first signal;
 - (b) band pass filtering the first signal, thereby generating a second signal; and
 - (c) normalizing the second signal, thereby generating the data;

and in which the tracking step comprises taking the derivative of the data.

MAS 77845 CONFIDENTIAL ATTORNEYS EYES ONLY

INTERNATIONAL SEARCH REPORT

PCT/IB 97/00292

. FIELDS Inhum o PC 6	to international Patent Classification(IPC) or to both national dassifi 3 SEARCHED cournentation searched (classification system lokowed by classifica		
IPC 6	ocumentation searched (classification system followed by classifica		• •
		tion symbols)	
	GOIN A61B		•
)ocumenti	abon searched other than minumum documentation to the extent that	t such documents are included in the fields ass	urched
Jedronc (data base consulted during the international search (name of data b	base and, where practical, search terms used)	
	•	•	
	·		
r DOCUM	MENTS CONSIDERED TO BE RELEVANT		····
Catedouk ,	Citation of document, with indication, where appropriate, of the ri	alevant passages	Relevant to claim No.
X	US 5 355 880 A (THOMAS ET AL.) 1	18 Uctober	1,7
A	see the whole document	·	17
	CD O COO COA A CHUTUEDCITY OF ME	PU MEVICO +	1-20
A	EP 0 522 674 A (UNIVERSITY OF NE SANDIA NATIONAL LABORATORIES) 13		1-28
	1993		•
	see the whole document		
A	WO 96 30742 A (CIBA CORNING DIAG	GNOSTICS	1-28
	CORP.) 3 October 1996		
	see the whole document		· · · · · · · · · · · · · · · · · · ·
A	US 5 435 309 A (THOMAS ET AL.)	25 July	1-28
•	1995		
	see the whole document	·	
•		-/	
		,	
	-1		
X) Fu	rther documents are listed in the combnustion of box C.	X Patent lamily members are listed to	n annex.
	salegones of cited documents :	Water Street Control of the Control	
-	pers defining the general state of the art which is not	 "I" ister document published after the inter or priority date and not in conflict with 	the application but
cons	idered to be of particular relevance r document but published on or after the international	cited to understand the principle of the stvention	•
	date	"X" document of particular relevance; the considered novel or cannot	
	n is exact to establish the publication date of another	"Y" document of particular relevance; the co	
	on or other special reason (as specified) ment retenting to an oral disclosure, use, exhibition or	cannot be considered to involve an im document is combined with one or mo	re other such docu-
	r means nent published prior to the international liling daté but	ments, such combination being obvious in the art.	
later	then the priority date claimed	"&" document member of the same patent	
Date of the	e actual completion of theirlernutronal search	Date of making of the international see	ел пероп
. 7	25 November 1997	08/12/1997	
Name and	mailing address of the ISA	Authorized officer	
	European Patent Office. P. S. 5818 Patentsaan 2 NL – 2280 MV Rijswyk Tel. (+31+70) 340–2040. Tx. 31 651 apo ni,		MAS 778
	Fax: (+31=70) 340=2040. 1 X 31 651 696 M;	Bosma, R	CONFIDENT ATTORNEYS EY

page 1 of 2

INTERNATIONAL SEARCH REPORT

intedonal	Application No
PCT/IB	97/00292

Catedon .	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 95 34806 A (LIESENHOFF, TIM ET AL.) 21 December 1995 see the whole document	1-6
A	DE 43 39 067 A (JENOPTIK GMBH) 18 May 1995 see the whole document	1-6
	·	
•		
	i i	
	·	
ŀ		
1		MAS 7 CONFIDI ATTORNEYS

page 2 of 2

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
☐ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
П отнер.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.